

# Clack®

## WS2CI

### WATER SPECIALIST CONTROL VALVE



Certified to NSF/ANSI/CAN 61 and NSF/ANSI/CAN 372.

- 2" Top mount control valve suited for commercial/industrial applications
- Epoxy coated lead free brass valve body
- Economical stainless steel optional meter assembly
- Service flow rate of 435 lpm (26.1 m<sup>3</sup>/h) (115 gpm), backwash 303 lpm (18.2 m<sup>3</sup>/h) (80 gpm)
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, days until next regeneration, volume remaining and current flow rate.
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Program in ppm, French degrees, German degrees, or cubic meters
- Fully programmable regeneration cycle sequence (maximum 9)
- Programmable regeneration cycle times
- Days override feature; 1-28 days available
- Coin Cell Lithium battery back-up with an 24 hour carry over
- Level VI 15-volt output DC power supply provides safe and easy installation
- Pre or Post treated water regenerant refill
- 24 Hour Clock
- Reliable and proven DC drive
- One piece expanding seal spacer stack assembly
- Linearly reciprocating piston operation



Optional 2" Meter

# Water Specialist 2" CI Control Specifications

Inlet/Outlet (1) .....	2" Female BSPT or NPT
Cycles .....	Up to 9
Valve Material .....	Lead free brass
Regeneration .....	Downflow

## CONTROL VALVE FLOW RATES

Service @ 1 bar/15 psi drop .....	435 lpm (26.1 m <sup>3</sup> /h) (115 gpm)
Backwash @ 1.7 bar/25 psi drop.....	303 lpm (18.2 m <sup>3</sup> /h) (80 gpm)
Cv Service .....	29.7
Cv Backwash .....	16.0

## OPERATING PRESSURES

Minimum/Maximum .....	1.4 - 8.6 bar (20 psi - 125 psi)
-----------------------	----------------------------------

## OPERATING TEMPERATURES

Minimum/Maximum .....	4° - 43° C (40° - 110° F)
-----------------------	---------------------------

## METER SPECIFICATIONS

Accuracy .....	± 5%
Flow Rate Range.....	5.7 - 568 lpm (1.5 - 150 gpm)
Volume Range .....	0.02 - 5,700 m <sup>3</sup>
Totalizer .....	1 - 99,999 m <sup>3</sup> (264 - 26,417,000 gallons)

## DIMENSIONS & WEIGHT

Distributor Pilot	
Valve bodies with 2" Female BSPT Inlet & Outlet.....	50mm OD
Valve bodies with 2" Female NPT Inlet & Outlet .....	1.90" OD (1.5" NPS)
Drain Line Connection .....	1.5" Female NPT
Brine Line Adapters Included.....	1" Male NPT elbow, ¾" x 1" solvent weld elbow and ½" OD Poly Tube Compression
Mounting Base .....	4" - 8 UN
Height From Top Of Tank.....	216 mm (8.5")
Shipping Weight With Meter .....	13 Kg (29 lbs.)

## ELECTRICAL SPECIFICATIONS

## POWER SUPPLY

	<u>U.S.</u>	<u>International</u>
Supply Voltage .....	100VAC to 120VAC ...	200VAC to 240VAC
Supply Frequency .....	50/60 Hz .....	50/60 Hz
Output Voltage .....	15VDC .....	15VDC
Output Current .....	500 mA .....	500 mA

## TANK APPLICATIONS

Water Softener .....	12" - 48" diameter
Water Filter (2).....	12" - 36" diameter

## CYCLES OF OPERATION

Choose up to nine regeneration cycles, in any order, with a wide range of available values:

Cycle	Range of values
Backwash.....	1 - 120 minutes
Rinse.....	1 - 120 minutes
Pause (service).....	1 - 480 minutes
Brine (co-current).....	1 - 180 minutes
Refill (softener) .....	0.1 - 99.0 minutes
Refill (filter) .....	0.1 - 99.0 minutes

### Options: Backwash Filter, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. See Distributor Pilot

2. Filter tank size calculated @ 407 lpm per m<sup>2</sup> of bed area /10 gpm of backwash per square foot of bed area